



Linear LED ceiling light IP65.

Flicker-free, anti-glare uniform industrial lighting.

Aluminum structure and polycarbonate.

I.D.S. technology for direct 24VDC connection.

The lamp can be installed on workbenches or mounted on ceilings as general industrial lighting.

Electrical features

Power supply	24 Vdc
LED driver 700mA	built-in
IEC class	III
Degree of protection	IP65
Connection	cable

Optical and mechanical features

LED type	minipower led
LED lifetime	50 000 h
Brightness	wide beam 120°
Light color	5000K CRI75
Structure	Aluminum
Covering	Polycarbonate diffuser
Lamp color	Aluminum
Operating temperature	-20 +55°C
Fastening	fastening accessories cod. JOB.FX01
Power cable	H05RN-F Neopren 2x0.75mmq: brown (+24Vdc) / blue (-24Vdc)

Model	Power supply	Current	Watt	Light color	Lumen LED	Weight /
JOBPL2	24 V dc	0,6 A	13 W	5000K CRI75	1400 lum 120°	0,90Kg / 1,98lb ~
JOBPL5	24 V dc	1,5 A	34 W	5000K CRI75	3500 lum 120°	1,80Kg / 3,97lb ~
JOBPL7	24 V dc	2,1 A	47 W	5000K CRI75	4900 lum 120°	2,60Kg / 5,73lb ~
JOBPL10	24 V dc	3,0 A	68 W	5000K CRI75	7000 lum 120°	3,40Kg / 7,50lb ~

DIMENSIONS (all values in millimeter / inch)

