



LED lamp made up of aluminum and ABS spot, n.1 power LED sources, adjustable lens, stainless-steel gooseneck arm covered by PVC, ABS base with fastening holes and on/off switch. Built-in LED driver. Power supply 230V 50/60Hz. Current 700mA.



**Applications:** particularly suitable for the precision lighting of sewing machines, stitching machines, eyeleting machines, key cutting machines.

**ELECTRICAL FEATURES**

Power supply	230Vac 50/60Hz
Voltage	3,8 Vdc
Current	700 mA dc
Power	3 W
IEC class	II
Driver LED	into base cod. A0481005060806B (vers. DIM cod. A0251005069917A)
Power cable	PVC L1,5m with Schuko plug

**MECHANICAL AND OPTICAL FEATURES**

LED type	Power LED
N. LED	1
LED lifetime	50.000 h
Brightness	Adjustable lens
Light colour	5000 K - CRI75
Fastening	4 screws
Switch	Unipolar on-off
Degree of protection	IP30
Colour	Black - RAL9002
Weight	1,40 Kg ~

**ORDER CODES**

Codes	L-arm	Power supply	Color
T13.70.N	700mm	230V	Black
T13.70.B	700mm	230V	White
T13.70.DIM.N	700mm	230V dimmer	Black
T13.70.DIM.B	700mm	230V dimmer	White



**Light flow from the surface**

H 220mm		H 500mm	
Current	350mA	Current	350mA
∅ (mm)	lux	∅ (mm)	lux
80	650	165	250
100	600	210	230
140	550	300	200

